


Flood Hazard Assessment
Intersection of Lake Macdonald Dr
and Dianella Crt
Cooroy
September 2024




The information contained in this report is subject to the disclaimers and definitions below.

*This document has been prepared solely for the benefit of **Noosa Council** and is issued in confidence for the purposes only for which it is supplied. Unauthorised use of this document in any form whatsoever is prohibited. No liability is accepted by HydraLogic or any employee, contractor, or sub-consultant of HydraLogic with respect to its use by any other person. This document may not be used, copied or reproduced in whole or part for any purpose other than that for which it was supplied by HydraLogic.*

This disclaimer shall apply notwithstanding that the document may be made available to other persons for an application for permission or approval to fulfil a legal obligation.

© HydraLogic 2024

Document Control Sheet	
Report Title	Flood Hazard Assessment Intersection of Lake Macdonald Dr and Dianella Crt Cooroy
Affected Properties	62 Lake Macdonald Dr Cooroy
RP Description	Lot 105 SP118458
Prepared For	Noosa Council
Date	04 September 2024
Report Status	Final v1.0
Author(s)	Damian McGarry
Qualification	BE Civil RPEQ MIEAust
Company	HydraLogic
Phone	07 5444 7444
Certified by	Damian McGarry
Industry Accreditation	RPEQ No. 06045
Signed	
Distribution	Glen Conforti

Document Path:	C:\Users\Damian\Dropbox\002_HydraLogic\001_Projects\030_NSC\010_General Enquiries\029_Cooroy Subdivision\006_Report\001_Draft\Flood Hazard Assessment Report Cooroy Subdivision dm 002.docx
----------------	---

CONTENTS

Executive Summary.....	1
1 Introduction	1
2 Available Data	3
3 Site Characteristics.....	4
3.1 Catchment Characteristics.....	4
4 Hydraulic Modelling.....	6
4.1 Model setup.....	6
4.1.1 Model boundaries	6
4.2 Future climate	6
4.3 Model Roughness	7
4.4 Validation.....	7
5 Flood Hazard	11
6 Sensitivity Analysis	17
6.1 Manning’s n roughness sensitivity	17
6.2 Culvert blockage sensitivity	19
7 Hydraulic Performance	22
8 Summary of findings	23
Appendices.....	1

FIGURES

Figure 1 - 50% AEP design discharge comparison.....	7
Figure 2 - 10% AEP design discharge comparison.....	8
Figure 3 - 2% AEP design discharge comparison.....	8
Figure 4 - 1% AEP design discharge comparison.....	8
Figure 5 - 1% AEP (2100) design discharge comparison	9
Figure 6 - 0.2% AEP design discharge comparison.....	9
Figure 7 - General flood hazard curves	11
Figure 8 - Duration of inundation Reference Point 1.....	13
Figure 9 - Duration of inundation Reference Point 2.....	13
Figure 10 - Sensitivity analysis +/- 25% Manning's n 2% AEP at Reference Pt A	17
Figure 11 - Sensitivity analysis +/- 25% Manning's n 1% AEP at Reference Pt A	18
Figure 12 - Sensitivity analysis +/- 25% Manning's n 0.2% AEP at Reference Pt A	18
Figure 13 - Sensitivity analysis 25% culvert blockage for 10% AEP at Reference Pt A	19
Figure 14 - Sensitivity analysis 50% culvert blockage for 2% AEP at Reference Pt A.....	20
Figure 15 - Sensitivity analysis 50% culvert blockage for 1% AEP at Reference Pt A.....	20
Figure 16 - Sensitivity analysis 50% culvert blockage for 0.2% AEP at Reference Pt A	21

EXECUTIVE SUMMARY

This report presents the findings of a flood hazard assessment undertaken for the road intersection of Lake Macdonald Dr and Dianella Crt in Cooroy.

This report describes the configuration of the local high resolution flood model and summarises the hydraulic performance of the intersection under a range of design flood conditions with Annual Exceedance Probabilities of between 50% AEP and 0.2 % AEP.

Detailed ground and feature survey provided by Murray & Associates (see **Appendix A**) shows three pipe culvert cells passing beneath Lake Macdonald Dr from the southeast corner of the intersection with Dianella Ct to the northwest corner of the intersection adjacent to Wilgee Ct. Two of pipe culverts are shown to be 1050 mm diameter and the third is 1350 mm diameter.

For the 10% AEP design flood event the intersection is not inundated and hence no flood hazard exists within the trafficable road corridor. For the 2% AEP design flood event, shallow inundation at the peak of the flood event introduces a low (H1) flood hazard classification across the intersection with areas of higher classification where flow across the road concentrates and returns to the main waterway, see **Map 5**. The flood hazard classifications are similar for the 1% AEP design flood event, however, a more prominent corridor of higher (H5) flood hazard exists across the intersection, see **Map 6**.

The duration of inundation across the intersection for the 2% AEP and 1% AEP design flood events is anticipated to be less than 1.5 hours. The actual duration of inundation will vary for each major rainfall event experienced in the local catchment; however, the approximate duration of the design flood event provides a reasonable indication of the duration of inundation which is also consistent with the size of the upstream catchment that contributes flood flows to the intersection location.

The intersection is flood free and trafficable for events up to the 10% AEP.

Detailed flood modelling of the catchment and subject intersection has demonstrated the capacity of the existing culverts provides 10% AEP design flood immunity to the intersection. For larger and rarer flood events of less than 2% AEP the model results show the intersection will experience water over the road to depths of less 0.3 m for a 1% AEP flood event for relatively short durations of less than 1.5 hours.

The flood modelling has also demonstrated that should a significant blockage of the culverts occur during a major rainfall flood event the depths of inundation across the culvert would not be expected to significantly change, however, the inundation across the intersection would persist for longer periods.

The hydraulic performance of the intersection culverts is summarised in **Table E -1** below.

Table E 1 - Hydraulic performance of intersection culverts

AEP		Discharge		Depth	Velocity	Water surface elevation*
		Culverts	Weir	Weir	Weir	
(%)	(1 in x)	(m ³ /s)	(m ³ /s)	(m)	(m/s)	(m AHD)
0.2	500	11.1	18.8	0.16	1.79	103.8
1 (2100)	100 (2100)	10.7	15.8	0.14	1.69	103.77
1	100	10.3	8.2	0.07	1.36	103.67
2	50	10.1	5.7	0.05	1.21	103.6
10	10	8.7	0	0.00	0.00	103.3
50	2	3.7	0	0.00	0.00	102.5

* Upstream face

1 INTRODUCTION

Noosa Council approached HydraLogic to provide a summary of the design flood conditions at the intersection of Lake Macdonald Drive and Dianella Court in Cooroy.

The crossing is portrayed as being inundated in Council's strategic planning and disaster management maps.

The watercourse and catchment associated with the culvert crossing at this location lie within the 2018 Six Mile Creek flood model prepared by WMA Water for Noosa Council.

An initial review of the flood model results revealed the local tributary was only defined in the flood study model to determine design flood inflows to the main branch of Six Mile Creek downstream of Cooroy township. The road culvert crossings along this local tributary were not defined in the flood model.

To enable a detailed summary of the design flooding conditions of the intersection to be prepared a higher resolution flood model was developed for the local tributary. This local flood model includes a higher resolution digital terrain model and the pipe culverts at Lake Macdonald Dr, Curlew Crescent, and Swift Drive.

This report describes the configuration of the local high resolution flood model and summarises the hydraulic performance of the intersection under a range of design flood conditions with Annual Exceedance Probabilities of between 50% AEP and 0.2 % AEP.

The intersection and local catchment are shown in **Map 1**.


C:\Users\Damian\Dropbox\002_HydraLogic\001_Projects\030_NSC\010_General Enquiries\029_Cooroy Subdivision\003_GIS\Six Mile Creek_Base_Cooroy_SubD.qgz Six Mile Creek_Base_Cooroy_SubD.qgz



LAKE MACDONALD DR
DIANELLA CT
INTERSECTION
FLOOD ASSESSMENT



- Study area
 - Cooroy Subdivision
 - Model catchment
 - Cadastre
 - Watercourses
 - Model Catchment
- QLD Globe Imagery**



HydraLogic

Date Created : 03.09.2024
Created by : DGM
Projection : EPSG:28356 GDA94 / MGA zone 56

Scale at A3
1: 5,000



Map Ref
1

Map Series

Location

2 AVAILABLE DATA

Table 2-1 presents a summary of the data utilised to inform this investigation.

Table 2-1 Available Data

Data	Source	Comments
Topographic details	2022 LiDAR Digital Elevation Model	Provided by Noosa Council
Catchment Boundaries	2018 Six Mile creek Flood Study 2022 DEM	
Land Use	Google Satellite	Determined from aerial image assessment
Hydrologic design flood runoff hydrographs	Watercourse flow hydrographs extracted from flood model results from the 2018 Six Mile Creek Flood Study	
Hydraulic tailwater boundary hydrographs	Watercourse stage hydrographs extracted from flood model results from the 2018 Six Mile Creek Flood Study	
Survey and infrastructure plans	Contour & Detail Survey of Lot 105 on SP 118458 62 Lake McDonald Drive, Cooroy prepared by Murray & Associates	Dated 05.04.24 Job number 100988 DTM See Appendix A
Road upgrade details	62 Lake Macdonald Drive, Cooroy prepared by Covey Associates Ptd Ltd	Issue A Dated 10.01.24 Job number 233467 C250 – 252 See Appendix B

3 SITE CHARACTERISTICS

The subject site is the intersection of Lake Macdonald Dr and Dianella Ct in Cooroy.

Detailed ground and feature survey provided by Murray & Associates shows three pipe culvert cells passing beneath Lake Macdonald Dr from the southeast corner of the intersection with Dianella Ct to the northwest corner of the intersection adjacent to Wilgee Ct. Two of pipe culverts are shown to be 1050 mm diameter and the third is 1350 mm diameter.


The Swift Drive culvert is a 1350 mm diameter and the Curlew Crs crossing is a 750 mm diameter.

Invert levels for these pipe culverts were determined from the 2022 digital elevation model (DEM).

3.1 Catchment Characteristics

Upstream of the subject site, the local catchment extends to the southeast and northeast and covers an area of approximately 70 hectares. The catchment is comprised of three sub-tributaries. The larger two of these sub-tributaries have a confluence downstream of Swift Dr and Curlew Crs. A third minor tributary drains from southwest and joins the main tributary watercourse approximately 450 m upstream of the subject site. There is also a minor inflow to the main tributary from the north just upstream of the subject site. The tributary waterway corridor is well defined by adjacent elevated topography.


C:\Users\Damian\Dropbox\002_HydraLogic\001_Projects\030_NSC\010_General Enquiries\029_Cooroy Subdivision\003_GIS\Six Mile Creek_Base_Cooroy_SubD.qgz Six Mile Creek_Base_Cooroy_SubD.qgz



LAKE MACDONALD DR
DIANELLA CT
INTERSECTION
FLOOD ASSESSMENT



- Cooroy Subdivision
 - Study area
 - Upstream catchment
 - Cadastre
 - Watercourses
 - Model Catchment
- DEM 2022 (mAHD)**
- 98
 - 112
 - 126
 - 140
 - 155
- QLD Globe Imagery**



HydraLogic

Date Created : 03.09.2024
Created by : DGM
Projection : EPSG:28356 GDA94 / MGA zone 56

Scale at A3 1: 5,000		Map Ref 2
-------------------------	--	--------------

Map Series
Digital Elevation Model

4 HYDRAULIC MODELLING

4.1 Model setup

To determine the potential flooding conditions of the Lake Macdonald Dr and Dianella Crt intersection a high-resolution HEC RAS (Version 6.5) 2D flood model was developed for the local catchment and watercourse.

The terrain base for the flood model was a 2022 digital elevation model provided by Noosa Council derived from aerial laser survey (LiDAR).

The flood model included the entire contributing local catchment area upstream of the subject site and extended approximately 450 m downstream to a confluence with another minor tributary.

A 2D model grid spacing of 5 m was adopted to ensure the accuracy of the terrain representation throughout the waterway corridor. The 5 m grid was tested against a 2m grid and produced consistent results.

Breaklines were incorporated to improve the model's representation of significant changes in surface elevation, land use and flow paths.

4.1.1 Model boundaries

To maintain consistency with the Six Mile Creek flood model, tailwater boundary conditions and upstream tributary flows were extracted from the model and applied to the high-resolution local flood model.

The downstream boundary of the local flood model was established as a time varying water level hydrograph. Upstream of the subject site time varying discharge hydrographs were also extracted from the Six Mile Creek flood model at five reference locations and used as inflow boundaries in the local model, see **Map 3**.

Design tailwater level and instream flow hydrographs were extracted from the Six Mile Creek flood model results for the following design flood events:

- 50% AEP (1 in 2 AEP)
- 10% AEP (1 in 10 AEP)
- 1% AEP (1 in 100 AEP)
- 1% AEP (1 in 100 AEP) 2100
- 0.2% AEP (1 in 500 AEP)

4.2 Future climate

As a part of the Six Mile Creek flood study, the Cooroy Creek flood model adopted a climate change/variability rainfall allowance of a 20% increase in rainfall intensity at year 2100.

4.3 Model Roughness

The observed land uses for the 2D model surface for the existing catchment condition is shown in **Map 3**.

The corresponding Manning’s n surface roughness values for each surface type are presented in **Table 4-1**.

Table 4-1 Flood model surface roughness

Catchment Surface	Assumed Manning’s n
Openspace	0.08
Residential	0.12
Rural residential	0.06
Waterway	0.12
Roads	0.015

4.4 Validation

Design discharge hydrographs were exported from the local high-resolution flood model results immediately upstream of the intersection and compared to design discharges extracted from the Cooroy Creek flood model.

Design discharge hydrographs show good consistency across all flood events. Refer to **Figure 1** to **Figure 6**.




Figure 1 - 50% AEP design discharge comparison




Figure 2 - 10% AEP design discharge comparison




Figure 3 - 2% AEP design discharge comparison




Figure 4 - 1% AEP design discharge comparison




Figure 5 - 1% AEP (2100) design discharge comparison





Figure 6 - 0.2% AEP design discharge comparison

LAKE MACDONALD DR
DIANELLA CT
INTERSECTION
FLOOD ASSESSMENT



- Sensitivity Ref Pt copy
- ▭ Study area
- ▭ Model catchment
- ▭ Cooroy Subdivision
- ▭ Cadastre
- - - Breaklines
- Inflow locations
- Regional tailwater boundary
- ▭ Model catchment
- Study Area Landuse**
- ▭ Openspace
- ▭ Residential
- ▭ Roads
- ▭ Rural Res
- ▭ Waterway
- QLD Globe Imagery**



HydraLogic

Date Created : 03.09.2024
Created by : DGM
Projection : EPSG:28356 GDA94 / MGA zone 56


Scale at A3
1: 5,000



Map Ref
3

Map Series

Local Flood Model Configuration



C:\Users\Damian\Dropbox\002_HydraLogic\001_Projects\030_NSC\010_General_Enquiries\029_Cooroy_Subdivision\003_GIS\Six Mile Creek_Base_Cooroy_SubD.qgz Six Mile Creek_Base_Cooroy_SubD.qgz

5 FLOOD HAZARD

Australian Rainfall and Runoff (ARR) A Guide to Flood Estimation, Book 6 – Flood Hydraulics presents a series of general flood hazard curves based on depth and velocity, see **Figure 7**. The flood hazard classifications of H1 to H6 describe the six classifications of flood hazard detailed in **Table 5-1**. The depth velocity flood hazard classification limits are presented in **Table 5-2**.




Figure 7 - General flood hazard curves

Table 5-1 Flood hazard classifications

Flood Hazard Classification	Description
H1	Generally safe for vehicles, people and buildings
H2	Unsafe for small vehicles
H3	Unsafe for vehicles, children and the elderly
H4	Unsafe for vehicles and people
H5	Unsafe for vehicles and people. All building types vulnerable to structural damage. Some less robust building types vulnerable to failure.
H6	Unsafe for vehicles and people. All building types considered vulnerable to failure.

Table 5-2 Depth and Velocity Vulnerability Threshold Classification Limits

Flood Hazard Classification	Classification limit (D and V in combination) m ² /s	Limiting still water depth (D) m	Limiting velocity (V) m/s
H1	$D*V \leq 0.3$	≤ 0.3	≤ 2.0
H2	$D*V \leq 0.6$	≤ 0.5	≤ 2.0
H3	$D*V \leq 0.6$	≤ 1.2	≤ 2.0
H4	$D*V \leq 1.0$	≤ 2.0	≤ 2.0
H5	$D*V \leq 4.0$	≤ 4.0	≤ 4.0
H6	$D*V > 4.0$	-	-

Flood hazards for the subject site intersection have been determined for the 10% AEP, 2% AEP, and 1% AEP design flood events in accordance with the guidance in ARR Book 6 and are presented in **Map 4 to Map 6**.

For the 10% AEP design flood event the intersection is not inundated and hence no flood hazard exists within the trafficable road corridor, see Map 4. For the 2% AEP design flood event, shallow inundation at the peak of the flood event introduces a H1 flood hazard classification across the intersection with areas of higher classification where flow across the road concentrates and returns to the main waterway, see Map 5. The flood hazard classifications are similar for the 1% AEP design flood event, however, a more prominent corridor of higher H5 flood hazard exists across the intersection, see Map 6.

Depth hydrographs were extracted from two reference points to determine the approximate duration of inundation that could be anticipated for inundation of the intersection. The depth hydrographs for the reference points shown on Map 6 are presented in **Figure 8** and **Figure 9**. The figures show the duration of inundation for the 2% AEP and 1% AEP design flood events to be less than 1.5 hours. The actual duration of inundation will vary for each major rainfall event experienced in the local catchment; however, the approximate duration of the design flood event provides a reasonable indication of the duration of inundation which is also consistent with the size of the upstream catchment that contributes flood flows to the intersection location.

The intersection is flood free and trafficable for events up to the 10% AEP.




Figure 8 - Duration of inundation Reference Point 1




Figure 9 - Duration of inundation Reference Point 2

LAKE MACDONALD DR
DIANELLA CT
INTERSECTION
FLOOD ASSESSMENT





- Cadastre
- Study area

Hazard 10% AEP

- H1
- H2
- H3
- H4
- H5
- H6

QLD Globe Imagery



HydraLogic

Date Created : 03.09.2024
Created by : DGM
Projection : EPSG:28356 GDA94 / MGA zone 56

Scale at A3

1: 900



Map Ref

4

Map Series

**10% AEP
Flood Hazard**

LAKE MACDONALD DR
DIANELLA CT
INTERSECTION
FLOOD ASSESSMENT






- Cadastre
- Study area

Hazard Classification

- H1
- H2
- H3
- H4
- H5
- H6

QLD Globe Imagery



HydraLogic

Date Created : 03.09.2024
Created by : DGM
Projection : EPSG:28356 GDA94 / MGA zone 56

Scale at A3		Map Ref
1: 900		5

Map Series: 2% AEP Flood Hazard

C:\Users\Damian\Dropbox\002_HydraLogic\001_Projects\030_NSC\010_General_Enquiries\029_Cooroy_Subdivision\003_GIS\Six Mile Creek_Base_Cooroy_SubD.qgz Six Mile Creek_Base_Cooroy_SubD.qgz

LAKE MACDONALD DR
DIANELLA CT
INTERSECTION
FLOOD ASSESSMENT






- Road Reference Pt
- Cadastre
- Study area

Hazard001 copy

- H1
- H2
- H3
- H4
- H5
- H6

QLD Globe Imagery



HydraLogic

Date Created : 03.09.2024
Created by : DGM
Projection : EPSG:28356 GDA94 / MGA zone 56

Scale at A3		Map Ref
1: 900		6

Map Series: 1% AEP Flood Hazard

C:\Users\Damian\Dropbox\002_HydraLogic\001_Projects\030_NSC\010_General_Enquiries\029_Cooroy_Subdivision\003_GIS\Six Mile Creek_Base_Cooroy_SubD.qgz

6 SENSITIVITY ANALYSIS

To test the sensitivity of the high-resolution local flood model to modest changes in adopted parameter values, two sensitivity tests were conducted. A reference point (A) was adopted at the road entrance to Dianella Crt where hydrographs were extracted from the flood model and compared to the base case results. See **Map 3** for reference point location.

6.1 Manning's n roughness sensitivity

The first sensitivity test was conducted using a +/- 25% variation in the adopted Manning's n surface roughness value for the model. The adopted Manning's n surface roughness values are shown in **Table 4-1**.

Water level (Depth) hydrographs were extracted from the results of each sensitivity analysis at reference point A and compared to the base case results for the 2% AEP, 1% AEP, and 0.2% AEP design flood events. See **Figure 10** to **Figure 12**.

The results show the design flood levels at the intersection are not sensitive to reasonable changes in the adopted Manning's n surface roughness.




Figure 10 - Sensitivity analysis +/- 25% Manning's n 2% AEP at Reference Pt A




Figure 11 - Sensitivity analysis +/- 25% Manning's n 1% AEP at Reference Pt A




Figure 12 - Sensitivity analysis +/- 25% Manning's n 0.2% AEP at Reference Pt A

6.2 Culvert blockage sensitivity

The second sensitivity test assumed an amount of blockage of the available waterway area of the three pipe culverts which pass beneath the subject site intersection. A blockage factor was applied based on the Australian Rainfall and Runoff Book 6 Chapter 6 guidelines. An assumed Debris Potential (DP) of *medium* was adopted and an L_{10} value of 1.5 m assumed. The smaller culvert pipe diameter of 1050 mm was applied as the inlet width (W) control dimension. Based on guidelines a blockage factor of 25% was applied to the 50% AEP and 10% AEP flood event, and 50% to the 2% AEP, 1% AEP, and 0.2% AEP flood events.

Water level (Depth) hydrographs were extracted from the results of each sensitivity analysis at reference point A and compared to the base case results for the 10% AEP, 2% AEP, 1% AEP, and 0.2% AEP design flood events. See **Figure 13** to **Figure 16**.

The results show that shallow inundation to a depth of approximately 100 mm is introduced at reference point A for the 10% AEP design flood event, see Figure 13. For the 2% AEP, 1% AEP, and 0.2% AEP design flood events inundation depths across the intersection at reference point A increase by approximately 120 mm to 150 mm with the durations of inundation also increasing to between 2 hours and 6 hours respectively.

The results demonstrate that for flood events with AEPs less than 10% flooding conditions across the intersection do not change significantly in depth, however, durations of inundation may be extended.




Figure 13 - Sensitivity analysis 25% culvert blockage for 10% AEP at Reference Pt A




Figure 16 - Sensitivity analysis 50% culvert blockage for 0.2% AEP at Reference Pt A

7 HYDRAULIC PERFORMANCE

The hydraulic performance of the waterway crossing intersection is summarised in **Table 7-1**.

The hydraulic performance is based on the adopted flood model parameters and does not include potential significant blockage of the culverts.

Table 7-1 - Hydraulic performance of intersection culverts

AEP		Discharge		Depth	Velocity	Water surface elevation*
		Culverts	Weir	Weir	Weir	
(%)	(1in x)	(m ³ /s)	(m ³ /s)	(m)	(m/s)	(m AHD)
0.2	500	11.1	18.8	0.16	1.79	103.8
1 (2100)	100 (2100)	10.7	15.8	0.14	1.69	103.77
1	100	10.3	8.2	0.07	1.36	103.67
2	50	10.1	5.7	0.05	1.21	103.6
10	10	8.7	0	0.00	0.00	103.3
50	2	3.7	0	0.00	0.00	102.5

* Upstream face


8 SUMMARY OF FINDINGS

Detailed flood modelling of the catchment and subject intersection has demonstrated the capacity of the existing culverts provides 10% AEP design flood immunity to the intersection. For larger and rarer flood events of less than 2% AEP the model results show the intersection will experience water over the road to depths of less 0.3 m for a 1% AEP flood event for relatively short durations of less than 1.5 hours.

The flood modelling has also demonstrated that should a significant blockage of the culverts occur during a major rainfall flood event the depths of inundation across the culvert would not be expected to significantly change, however, the inundation may persist for longer periods.

APPENDICES

Appendix A - Contour & Detail Survey prepared by Murray & Associates



NOTE:
 1. Sewer & Stormwater pipe IL's & diameters have been plotted from council records and field measurements.
 2. Meridian is MGA (Zone 56) vide SP176968

MURRAY & ASSOCIATES
 SURVEYORS & TOWN PLANNERS
 ACN 075 543 154
 Murray Building, 15-17 Currie St. Nambour Ph. (07)5441 2188 P.O. Box 246
 Branch Offices at Maroochydore Caboolture Chinchilla Roma Gympie & Emerald

AV	Air Valve	PH	Fire Hydrant	T	Tree	—	Telecommunications Line
BM	Bench Mark	GRATE	Stormwater Grate	TE	Telstra Pit	—	Sewer Line
CP	Control Point	GATE	Gate	TP	Telstra Pillar	—	Water Line
ELP	Elect. Light Pole	S	Sign	W	Water Meter	—	Fenceline
EMH	Electricity Manhole	GAS	Gas Infrastructure	WV	Water Valve	—	Electricity
PP	Power Pole	SMH	Sewer Manhole	—	—	—	Gas Line
EPI	Electricity Pillar	SV	Scower Valve	—	—	—	Edge of Bitumen
EPT	Electricity Pit	SMWH	Stormwater Manhole	—	—	—	Tree line
						—	Underground Electricity
						—	Stormwater
						—	Overhead Powerline

NO.	DESCRIPTION	DATE	INIT.


PROJECT
 Contour & Detail Survey of
 Lot 105 on SP 118458
 62 Lake McDonald Drive,
 Cooroy
 L.G.A. Noosa Shire Council

CLIENT
 Noosa Shire Council


Notes: Contour Interval is 0.5 metres. Underground services have been located from visible surface features only. A Dial Before You Dig search should be performed before the commencement of any excavation work. The property boundaries shown have not fully been investigated for the purpose of this survey. For an accurate determination of the boundaries, an Identification survey will be required.

Datum: PSM 176243 RL 108 138 Form 6 Dated 29.02.24	F.W.: CAC	Date: 05.04.24
Drawn: CAC	Level Bk: F.Bk	File: 100988
Licd. Surveyor Ian Smith	Acc. Bk: -	Job & Plan No.: 100988 DTM
	Scale: A1 1:500	

Appendix B - Road upgrade details prepared by Covey Associates Ptd Ltd




IT IS THE RESPONSIBILITY OF THE CONTRACTOR TO CONTACT THE RELEVANT AUTHORITIES TO CONFIRM THE LOCATION OF ALL EXISTING SERVICES PRIOR TO THE COMMENCEMENT OF EXCAVATION



LEGEND

	PROPOSED LINEMARKING
	EXISTING LINEMARKING TO REMAIN
	PROPOSED SAWCUT LINE
	EDGE OF BITUMEN
	YELLOW BIDIRECTIONAL RRPM
	YELLOW UNIDIRECTIONAL RRPM
	PROPOSED ASPHALT ROAD
	PROPOSED CONCRETE FOOTPATH
	PROPOSED CONCRETE DRIVEWAY
	BIORETENTION BASIN FILTER SURFACE
	LAND RESUMPTION
	PROPOSED STORMWATER DRAINAGE
	PROPOSED Ø150 PVC-O PN16 WATER MAIN
	PROPOSED Ø150 UPVC SEWER MAIN
	EXISTING UNDERGROUND STORMWATER DRAINAGE
	EXISTING WATER MAIN
	EXISTING COMMUNICATIONS CABLES
	EXISTING UNDERGROUND ELECTRICAL
	EXISTING OVERHEAD ELECTRICAL
	EXISTING SITE BOUNDARY
	DESIGN SURFACE CONTOURS (250mm INTERVALS)
	EXISTING SURFACE CONTOURS (250mm INTERVALS)



NOTE:
ALL LINE MARKING AND DELINEATION TO BE IN ACCORDANCE WITH THE MANUAL OF UNIFORM TRAFFIC CONTROL DEVICES (MUTCD)



Check all dimensions before commencement of work. Check Site boundary dimensions from the Title plans. Check Building Boundary clearances by set out. Notwithstanding the information supplied on this drawing, the location, depth and extent of underground or overhead services are to be confirmed and protected on site by the contractor prior to commencement of works.

Checked - CT	
Design - SK	Drawn - SK
Scales - AS SHOWN	
Document Stage - APPROVAL	
A 100124	ISSUE FOR CLIENT REVIEW
Issue Date	Description
	By



Consulting Civil & Structural Engineers
Project Management & Planning
124 DUPORTH AVENUE
PO BOX 16
MAROOCHYDORE QLD 4558
E-MAIL: engineers@covey.com.au
Ph (07) 5443 7777
Fax (07) 5443 7577


Drawing title -
EXTERNAL ROADWORKS DETAIL - SHEET 1

Project - **COMMUNITY AFFORDABLE HOUSING DEVELOPMENT**
Client - **NOOSA COUNCIL**

Site - **62 LAKE MACDONALD DRIVE, COOROY**


Project No. 233467 Sheet No. C250
Digital Ref: C250-C251 EXTERNAL ROADWORKS DETAILS Issue: A
This Document is copyright and shall not be copied without written approval, nor shall it be used except for the Development and the Site Specified.
Plot 7 June 2024 - 11:05 AM

IT IS THE RESPONSIBILITY OF THE CONTRACTOR TO CONTACT THE RELEVANT AUTHORITIES TO CONFIRM THE LOCATION OF ALL EXISTING SERVICES PRIOR TO THE COMMENCEMENT OF EXCAVATION



LEGEND	
	PROPOSED LINEMARKING
	EXISTING LINEMARKING TO REMAIN
	PROPOSED SAWCUT LINE
	EDGE OF BITUMEN
	YELLOW BIDIRECTIONAL RRPM
	YELLOW UNIDIRECTIONAL RRPM
	PROPOSED ASPHALT ROAD
	PROPOSED CONCRETE FOOTPATH
	PROPOSED CONCRETE DRIVEWAY
	BIORETENTION BASIN FILTER SURFACE
	LAND RESUMPTION
	PROPOSED STORMWATER DRAINAGE
	PROPOSED Ø150 PVC-O PN16 WATER MAIN
	PROPOSED Ø150 UPVC SEWER MAIN
	EXISTING UNDERGROUND STORMWATER DRAINAGE
	EXISTING WATER MAIN
	EXISTING COMMUNICATIONS CABLES
	EXISTING UNDERGROUND ELECTRICAL
	EXISTING OVERHEAD ELECTRICAL
	EXISTING SITE BOUNDARY
	DESIGN SURFACE CONTOURS (250mm INTERVALS)
	EXISTING SURFACE CONTOURS (250mm INTERVALS)

NOTE:
ALL LINE MARKING AND DELINEATION TO BE IN ACCORDANCE WITH THE MANUAL OF UNIFORM TRAFFIC CONTROL DEVICES (MUTCD)



Check all dimensions before commencement of work.
Check Site boundary dimensions from the Title plans
Check Building Boundary clearances by set out.
Notwithstanding the information supplied on this drawing,
the location, depth and extent of underground or overhead
services are to be confirmed and protected on site by the
contractor prior to commencement of works.

Checked - CT	
Design - SK	Drawn - SK
Scales - AS SHOWN	
Document Stage - APPROVAL	
A	100124 ISSUE FOR CLIENT REVIEW
Issue Date	Description
By	

COVEY ASSOCIATES PTY LTD
 Consulting Civil & Structural Engineers
 Project Management & Planning
 124 DUPORTH AVENUE
 PO BOX 16
 MAROOCHYDORE QLD 4558
 E-MAIL: engineers@covey.com.au
 Ph (07) 5443 7777
 Fax (07) 5443 7577

Approved
 Drawing title -
EXTERNAL ROADWORKS DETAIL - SHEET 2

Project - **COMMUNITY AFFORDABLE HOUSING DEVELOPMENT**
 Client - **NOOSA COUNCIL**

Site - **62 LAKE MACDONALD DRIVE, COOROY**

Project No. **233467** Sheet No. **C251**
 Digital Ref: **C250-C251 EXTERNAL ROADWORKS DETAILS** Issue: **A**

This Document is copyright and shall not be copied without written approval, nor shall it be used except for the Development and the Site Specified.

End of Report